

Phat-Neut® Quick Reference Table

Dilutions, Dry-On® and Lift-Mode® use scenarios

Shake bottle well for 10 seconds before use. Mix or shake into any dilution vigorously for 20 seconds. Dry-On® is only for heavy, continuous exterior dirt film. Lift-Mode® is the normal wet application method.

Use scenarios and dilution guide

Use scenario	Mode	Dilution	Ratio	Allow to dry?	Application notes
Heavy exterior traffic film	Dry-On®	2-4%	1:50-1:25	Yes - only into heavy dirt film	Use only where there is continuous, absorbent dirt film. Apply by pump sprayer preferably, or trigger. Allow to visibly dry into the dirt, then rinse immediately.
Dirty lower panels, sills and wheel areas	Dry-On®	2-4%	1:50-1:25	Yes - only into heavy dirt film	Test first with a small drop. If it spreads and absorbs into the dirt film, Dry-On® may be used.
Wheels with heavy dirt film	Dry-On® or Lift-Mode®	10%	1:10	Dry-On® only if heavy continuous dirt film is present	Use 10% in a pump sprayer or trigger. Use Dry-On® only where sufficient heavy dirt film is present. Otherwise use wet and rinse.
Upper panels with normal traffic film	Lift-Mode®	2%	1:50	No	Apply wet to soften, lift and encapsulate grime. Work panel by panel and do not allow to dry.
Rinseless pre-treatment	Lift-Mode®	2%	1:50	No	Spray onto dry panels before the bucket wash to add lubrication and loosen contamination. Do not use Dry-On®.
Rinseless bucket wash	Lift-Mode®	0.4%	1:250	No	Standard bucket wash dilution. Mix vigorously for at least 20 seconds.
Rinseless bucket wash - extra lubrication	Lift-Mode®	0.5%	1:200	No	Use where extra lubrication is wanted. Do not allow to dry.
Light hard-surface cleaning	Lift-Mode®	0.5%	1:200	No	Use with distilled water where possible. Apply by trigger spray or damp microfibre towel. Do not allow to dry.
Insect and bird dropping removal	Lift-Mode®	4%	1:25	No	Apply liberally, allow to soak, then rinse or wipe safely. Do not use Dry-On®.
Clay lubricant	Lift-Mode®	1-2%	1:100-1:50	No	Keep surface wet during use.
Interior hard surfaces	Lift-Mode® only	0.5%	1:200	No	Use only on suitable hard surfaces after testing. Apply via microfibre rather than spraying directly. Do not use on soft furnishings.

Dry-On® and Lift-Mode® rule summary

Rule	Dry-On®	Lift-Mode®
Intended purpose	Severe exterior dirt film	Normal wet cleaning
Dirt level required	Heavy, continuous, absorbent dirt film	Light to medium dirt, normal wash stages
Product allowed to dry	Yes - only into suitable heavy dirt film	No
Suitable for clean or lightly soiled panels	No	Yes, if used wet
Suitable for interiors	No	Hard surfaces only, after testing
Panel temperature	Maximum 50°C and not hot or uncomfortably hot to touch	Work panel by panel in warm conditions; do not allow to dry
Rinse/removal	Pressure rinse preferred; low-pressure rinse plus bucket wash possible	Rinse, wipe or bucket wash while wet

Dry-On® is a controlled severe-dirt function, not a general drying instruction. Use it only after the dirt level is confirmed suitable, and follow the instructions. For normal rinseless washing, use Lift-Mode®.

Bilt-Hamber Laboratories - Phat-Neut® quick reference