

PROFESSIONAL FINAL FINISH



Page: 1
Compilation date: 21.09.2021

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PROFESSIONAL FINAL FINISH

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC31: Polishes and wax blends.

1.3. Details of the supplier of the safety data sheet

Company name: Infinitec GmbH

Matzenberg 171 Saarbrücken D-66115

Germany

Tel: +4968198 800306

Email: a.neuner@infinitec-gmbh.de

1.4. Emergency telephone number

Emergency tel: Medical Emergency information in case of poisoning: Poison Information Center Mainz -

24h - Phone: +49 (0) 6131 19240 (advisory service in German or English language)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Corr. 1A: H314

Most important adverse effects: Causes severe skin burns and eye damage.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.Hazard pictograms: GHS05: Corrosion



Signal words:	Danger
Precautionary statements:	P102: Keep out of reach of children.
	P260: Do not breathe dust/fume/gas/mist/vapours/spray.
	P280: Wear protective gloves/protective clothing/eye protection/face protection.
	P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
	P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.
	Rinse skin with water .



PROFESSIONAL FINAL FINISH



Page: 2

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

2-BUTOXYETHANOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-905-0	111-76-2	-	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315	1-10%

1-PROPANAMINIUM, 3-AMINO-N-(CARBOXYMETHYL)-N,N-DIMETHYL-, N-COCO ACYL DERIVS., HYDROXIDES, INNER SALTS

263-058-8	61789-40-0	-	Eye Dam. 1: H318; Aquatic Acute 1:	<1%
			H400; Aquatic Chronic 3: H412	

HYDROGEN CHLORIDE

231-595-7	7647-01-0	-	Acute Tox. 3: H331; Skin Corr. 1A:	<1%
			H314; Press. Gas: H280	

Section 4: First aid measures

4.1. Description of first aid measures Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

- **Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
 - Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.
 - Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.



PROFESSIONAL FINAL FINISH



Page: 3

Ingestion:	Corrosive burns may appear around the lips. Blood may be vomited. There may be
	bleeding from the mouth or nose.
Inhalation:	There may be shortness of breath with a burning sensation in the throat. Exposure may
	cause coughing or wheezing.
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.
4.3. Indication of any immedi	ate medical attention and special treatment needed
Immediate / special treatment:	Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

PROFESSIONAL FINAL FINISH



Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

Hazardous ingredients:

2-BUTOXYETHANOL

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation	246 mg/m	Workers	Local
DNEL	Inhalation	89 mg/kg	Workers	Systemic
DNEL	Inhalation	1,091 mg/m	Workers	Systemic
DNEL	Inhalation	125 mg/kg	Workers	Systemic
DNEL	Inhalation	98 mg/m	Workers	Systemic
PNEC	Fresh water	8,8 mg/l	-	-
PNEC	Marine water	0,88 mg/l	-	-
PNEC	Microorganisms in sewage treatment	463 mg/l	-	-
PNEC	Soil (agricultural)	2,33 mg/kg	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

pH: 2,7

9.2. Other information

Other information: No data available.



PROFESSIONAL FINAL FINISH



Page: 5

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2-BUTOXYETHANOL

IVN	RAT	LD50	307	mg/kg
ORL	MUS	LD50	1230	mg/kg
ORL	RAT	LD50	470	mg/kg

1-PROPANAMINIUM, 3-AMINO-N-(CARBOXYMETHYL)-N,N-DIMETHYL-, N-COCO ACYL DERIVS., HYDROXIDES, INNER SALTS

DERMAL	RBT	LD50	>2000	mg/kg
ORAL	RAT	LD50	2335	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Nanolex Car Care Matzenberg 171 66115 Saarbrücken Tel.: +49 681. 906 776 50

SAFETY DATA SHEET

PROFESSIONAL FINAL FINISH



Page: 6

Inhalation:	iere may be shortness of breath with a burning sensation in the throat. Exposure m	lay

cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

1-PROPANAMINIUM, 3-AMINO-N-(CARBOXYMETHYL)-N,N-DIMETHYL-, N-COCO ACYL DERIVS., HYDROXIDES, INNER SAL

FISH	96H LC50	472-500	mg/l
------	----------	---------	------

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.



PROFESSIONAL FINAL FINISH



Page: 7

Section 16: Other information

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation EU) 2015/830 indicates text in the SDS which has changed since the last revision.
indicates text in the SDS which has changed since the last revision.
-
H302 [,] Harmful if swallowed
H312: Harmful in contact with skin.
1314: Causes severe skin burns and eye damage.
1315: Causes skin irritation.
1318: Causes serious eye damage.
1319: Causes serious eye irritation.
H331: Toxic if inhaled.
1332: Harmful if inhaled.
1400: Very toxic to aquatic life.
1412: Harmful to aquatic life with long lasting effects.
The above information is believed to be correct but does not purport to be all inclusive
and shall be used only as a guide. This company shall not be held liable for any
lamage resulting from handling or from contact with the above product.
+ + + + + + +