GYEON Q² Trim EVO

Revision date: 05.12.2023

Product code: G0043

Page 1 of 18

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

GYEON Q² Trim EVO

Further trade names

GYEON Q² Trim

UFI:

CUV7-J6PC-Y005-X5UN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Vehicle protective product - coating designed for leather upholstery. Enthusiasts and professional use (End consumer)

Uses advised against

Any non-intended use.

1.3. Details of the supplier of the safety data sheet

Manufacturer		
Company name:	Gyeon Technology	
Street:	1405-538, 212, Gasan digital 1-ro	
Place:	Geumcheon-gu, Seoul, Korea	
Telephone:	+82-10-4339-3599	
Contact person:	Robert Gyeon	
E-mail:	sales@gyeon.co	
Supplier		
Company name:	Gyeon UK Ltd	
Street:	Commercial Quay, 84 Commercial Str	ree
Place:	GB-EH6 6LX Edinburgh	
E-mail:	hello@gyeonquartz.uk	
Contact person:	Richard Cooper	Telephone:+44 (0)7984 056790
<u>1.4. Emergency telephone</u> number:	National Poisons Information Service professionals only'.	- 03448920111. 'For healthcare

Further Information

Safety Data Sheet according to UK-REACH Regulation

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT RE 2; H373 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

stoddard solvent; Low boiling point naphtha - unspecified Naphtha (petroleum), light alkylate; Low boiling point modified naphtha toluene

GYEON Q² Trim EVO

Product code: G0043 Revision date: 05.12.2023 Page 2 of 18 Signal word: Danger Pictograms: Hazard statements H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eve irritation. H373 May cause damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects. **Precautionary statements** P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 Do NOT induce vomiting. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. 2.3. Other hazards The mixture contains the following substances fulfilling the PBT criteria according to UK REACH: Hexamethyldisiloxane; octamethylcyclotetrasiloxane. The mixture contains the following substances fulfilling the vPvB criteria according to UK REACH: Decamethylcyclopentasiloxane; octamethylcyclotetrasiloxane. Endocrine disrupting properties: Decamethylcyclopentasiloxane; octamethylcyclotetrasiloxane.

This product does not contain a substance (> 0,1 %) that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The substance is included in one of the lists of endocrine disruptors (list II (human.)).

In use, may form flammable/explosive vapour-air mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation)				
541-02-6	Decamethylcyclopentasiloxane			20 - < 25 %	
	208-764-9				
69430-37-1	Aminoalkoxydimethylpolysiloxane		12 - < 15 %		
	628-867-6				
	Flam. Liq. 2, Skin Irrit. 2, Eye Irrit. 2				
8052-41-3	stoddard solvent; Low boiling point naphtha - unspecified			7 - < 10 %	
	232-489-3	649-345-00-4			
	Flam. Liq. 3, STOT RE 1, Asp. Tox	. 1, Aquatic Chronic 2; H226 H372 F	I304 H411		
64741-66-8	Naphtha (petroleum), light alkylate;	Low boiling point modified naphtha		5 - < 7 %	



GYEON Q² Trim EVO

Revision date: 05.12.2023

Product code: G0043

Page 3 of 18

	265-068-8	649-276-00-X	
	Asp. Tox. 1; H304	•	
546-68-9	Titanium tetraisopropanola	e	1 - < 3 %
	208-909-6		
	Flam. Liq. 3, Eye Irrit. 2, S	OT SE 3; H226 H319 H336	
1330-20-7	xylene		1 - < 3 %
	215-535-7	601-022-00-9	
	Flam. Liq. 3, Acute Tox. 4,	Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315	
108-88-3	toluene		1 - < 3 %
	203-625-9	601-021-00-3	
	Flam. Liq. 2, Repr. 2, Skin H373 H304	rrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H225 H361d I	H315 H336
107-46-0	Hexamethyldisiloxane		1 - < 3 %
	203-492-7		
	Flam. Liq. 2, Aquatic Acute		
67-56-1	methanol	0.5 - < 1 %	
	200-659-6	603-001-00-X	
	Flam. Liq. 2, Acute Tox. 3,	Acute Tox. 3, Acute Tox. 3, STOT SE 1; H225 H331 H311	H301 H370
25550-14-5	Ethyltoluene	0.3 - < 0.5 %	
	247-093-6		
	Flam. Liq. 3, Repr. 2, Skin	rrit. 2, Eye Irrit. 2, Aquatic Chronic 2; H226 H361f H315 H3	19 H411
100-41-4	ethylbenzene		0.2 - < 0.3 %
	202-849-4	601-023-00-4	
	Flam. Liq. 2, Acute Tox. 4, H412	STOT RE 2, Asp. Tox. 1, Aquatic Chronic 3; H225 H332 H3	373 H304
556-67-2	octamethylcyclotetrasiloxa	0.1 - < 0.2 %	
	209-136-7	014-018-00-1	
	Repr. 2, Aquatic Chronic 1	H361f H410	
98-82-8	cumene	< 0.1 %	
	202-704-5	601-024-00-X	
	Flam. Liq. 3, Carc. 1B, ST	DT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H350 H335	H304 H411

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity			
	Specific Cond	. Limits, M-factors and ATE				
541-02-6	208-764-9	Decamethylcyclopentasiloxane	20 - < 25 %			
	inhalation: L0 > 5000 mg/kg	C50 = 7,3 - 10,32 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 =				
69430-37-1	628-867-6	628-867-6 Aminoalkoxydimethylpolysiloxane				
	oral: LD50 = >5000 mg/kg					
1330-20-7	215-535-7	xylene	1 - < 3 %			
	inhalation: LC50 = (6700) mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = (12126) mg/kg; oral: LD50 = (3523) mg/kg					
108-88-3	203-625-9	toluene	1 - < 3 %			
	inhalation: LC50 = (28,1) mg/l (vapours); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg					
67-56-1	7-56-1 200-659-6 methanol					



GYEON Q² Trim EVO

Revision date	e: 05.12.2023	Product code: G0043	Page 4 of 18		
100-41-4	100-41-4 202-849-4 ethylbenzene				
	inhalation: LC50 = 17,2 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = >15000 mg/kg; oral: LD50 = 3500 mg/kg				
556-67-2	209-136-7	octamethylcyclotetrasiloxane	0.1 - < 0.2 %		
	Aquatic Chronic 1; H410: M=10				
98-82-8	202-704-5	cumene	< 0.1 %		
	inhalation: LC5	50 = 39 mg/l (vapours); dermal: LD50 = 12300 mg/kg			

Further Information

stoddard solvent; Low boiling point naphtha - unspecified:

Note P: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0.1 % w/w benzene (Einecs No 200-753-7).

This mixture contains the following substances of very high concern (SVHC) which are included in the Candidate List according to Article 59 of REACH: Decamethylcyclopentasiloxane, octamethylcyclotetrasiloxane

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Take off immediately all contaminated clothing. First aider: Pay attention to self-protection!

After inhalation

Remove person to fresh air and keep comfortable for breathing. In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation can cause damage to the respiratory tract or lungs.

May be fatal if swallowed and enters airways.

following inhalation: Headache. spasms. Repeated exposure may cause skin dryness or cracking. Caution if victim vomits: Risk of aspiration!

Causes skin irritation.

Repeated exposure may cause skin dryness or cracking.

Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Subsequent observance for pneumonia and lung oedema.

SECTION 5: Firefighting measures

according to UK REACH Regulation

GYEON Q² Trim EVO

Revision date: 05.12.2023

Product code: G0043

Page 5 of 18

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Dry extinguishing powder. Alcohol resistant foam. In case of major fire and large quantities: Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Can be released in case of fire: Gas/vapours, irritant. Carbon monoxide (CO). Carbon dioxide (CO2).

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes. Reignition possible over considerable distance.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Use water spray jet to protect personnel and to cool endangered containers. In case of major fire and large guantities: Evacuate area. Fight fire remotely due to the risk of explosion.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Safe handling: see section 7 Personal protection equipment: see section 8 Keep away from sources of ignition - No smoking.

For non-emergency personnel

Remove persons to safety. Remove all sources of ignition. Ventilate affected area. Wear personal protection equipment. (See section 8.)

For emergency responders

No special measures are necessary.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Danger of explosion! Cover drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Ventilate affected area.

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaustion at critical locations. Do not breathe gas/vapour/aerosol.Avoid contact with skin, eyes and clothes. Wear suitable protective clothing. (See section 8.)



according to UK REACH Regulation

GYEON Q² Trim EVO

Revision date: 05.12.2023

Product code: G0043

Page 6 of 18

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Flammable vapours can accumulate in head space of closed systems. In use, may form flammable/explosive vapour-air mixture. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

The usual precautions for handling chemicals should be considered.

Keep away from food, drink and animal feedingstuffs.

Always close containers tightly after the removal of product. When using do not eat, drink or smoke. Wash hands before breaks and after work. Protect skin by using skin protective cream. Take off contaminated clothing and wash it before reuse.

Further information on handling

General protection and hygiene measures: See section 8.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Protect against direct sunlight.

Ensure adequate ventilation of the storage area.

Make sure spills can be contained (e.g. sump pallets or kerbed areas).

Hints on joint storage

Do not store together with: Gas. Explosives. Flammable solids. Pyrophoric liquids and solids. Self-heating substances and mixtures. Substances and mixtures which, in contact with water, emit flammable gases. Oxidizing liquids. Oxidizing solids. ammonium nitrate. Self-reactive substances and mixtures. Organic peroxides. Non-combustible toxic substances. Radioactive substances. Infectious substances.

Further information on storage conditions

Keep the packing dry and well sealed to prevent contamination and absorbtion of humidity. Protect against: UV-radiation/sunlight. heat. Humidity frost. storage temperature: 15 - 25°C

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
98-82-8	Cumene	25	125		TWA (8 h)	WEL
		50	250		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
67-56-1	Methanol	200	266		TWA (8 h)	WEL
		250	333		STEL (15 min)	WEL
108-88-3	Toluene	50	191		TWA (8 h)	WEL
		100	384		STEL (15 min)	WEL
25551-13-7	Trimethylbenzenes: mixed isomers	25	125		TWA (8 h)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)



		GYEON Q ² Trim EVO	C			
Revision date: 05.12.2023Product code: G0043Page 7 of 1						
CAS No	Substance	Parameter	Value	Test material	Sampling time	
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol		Post shift	

8.2. Exposure controls











Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment.

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Recommended eye protection brand: Tightly sealed safety glasses. (BS/EN 166)

Hand protection

In case of prolonged or frequently repeated skin contact: Wear suitable gloves.

Suitable material: Butyl rubber.

Thickness of glove material: 0,5 mm

Breakthrough time >= 480 min. Penetration time (maximum wearing period): ~ 120 min. (estimated)

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The selected protective gloves have to satisfy the specifications of the Personal Protective Equipment at Work (Amendment) Regulations 2022 and the standard EN ISO 374.

Before using check leak tightness / impermeability. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Wear fire/flame resistant/retardant clothing.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

Generation/formation of aerosols

Exceeding exposure limit values

Insufficient ventilation

Suitable respiratory protective equipment: Combination filtering device (EN 14387) Type: A/P1-3

Half-face mask or quarter facepiece: maximum use concentration for substances with exposure limits: P1 filter: up to a max. of 4 times the exposure limit. P2 filter: up to a max. of 10 times the exposure limit. P3 filter: up to a max. of 30 times the expo.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Environmental exposure controls

Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid		
Colour:	colourless		
Odour:	like Petroleum		
Odour threshold:	not determined		

according to UK REACH Regulation

GYEON Q² Trim EVO

Revision date: (05.12.2023
------------------	------------

Product code: G0043

Page 8 of 18

			Test method
	Melting point/freezing point:	not determined	
	Boiling point or initial boiling point and	102 °C	
	boiling range:		
	Flammability:	not determined	
	Lower explosion limits:	not determined	
	Upper explosion limits:	not determined	
	Flash point:	12 °C	ISO 3679
	Auto-ignition temperature:	not determined	
	Decomposition temperature:	not relevant	
	pH-Value:	not determined	
	Viscosity / kinematic:	not determined	
	Water solubility:	insoluble	
	Solubility in other solvents		
	not determined		
	Dissolution rate:	not relevant	
	Partition coefficient n-octanol/water:	SECTION 12: Ecological information	
	Dispersion stability:	not relevant	
	Vapour pressure:	not determined	
	Density:	not determined	
	Bulk density:	not relevant	
	Relative vapour density:	not determined	
	Particle characteristics:	not relevant	
<u>9.2</u>	. Other information		
	Information with regard to physical hazard classes		
	Explosive properties		
	In use, may form flammable/explosive vapour-air mix	ture.	
	Self-ignition temperature		
	Gas:	not determined	
	Oxidizing properties		
	none.		
	Other safety characteristics		
	Evaporation rate:	not determined	
	Solvent separation test:	not determined	
	Solvent content:	50-100	
	Solid content:	not determined	
	Sublimation point:	not relevant	
	Softening point:	not relevant	
	Pour point:	not relevant	
	Viscosity / dynamic:	not determined	
	Flow time:	not determined	
	Further Information		
	No information available.		

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

GYEON Q² Trim EVO

Revision date: 05.12.2023

Product code: G0043

Page 9 of 18

No hazardous reaction when handled and stored according to provisions. Refer to chapter 10.5.

10.4. Conditions to avoid

Keep away from heat. Danger of explosion! In use may form flammable/explosive vapour-air mixture. Heating causes rise in pressure with risk of bursting.

10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. Reducing agents, strong. Strong acid. strong alkalis.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

No data available.

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) 13360 mg/kg; ATE (dermal) 27367 mg/kg; ATE (inhalation vapour) 273,7 mg/l; ATE (inhalation dust/mist) 42,61 mg/l

CAS No	Chemical name								
	Exposure route	Dose		Species	Source	Method			
541-02-6	Decamethylcyclopentasiloxane								
	oral	LD50 mg/kg	> 5000	Rat	ECHA Dossier				
	dermal	LD50 mg/kg	> 2000	Rabbit	ECHA Dossier				
	inhalation (4 h) dust/mist	LC50 10,32 mg/l	7,3 -	Rat	ECHA Dossier				
69430-37-1	Aminoalkoxydimethylpol	ysiloxane							
	oral	LD50 mg/kg	>5000	Rat.	read across				
1330-20-7	xylene								
	oral	LD50 mg/kg	(3523)	Rat	Study report (1986)	EU Method B.1			
	dermal	LD50 mg/kg	(12126)	Rabbit	Publication (1962)	Single dermal dose under occlusion follo			
	inhalation (4 h) vapour	LC50 mg/l	(6700)	Rat	Toxicol Appl Pharmacol 33:543-558. (1975	EU Method B.2			
	inhalation dust/mist	ATE	1,5 mg/l						
108-88-3	toluene								
	oral	LD50 mg/kg	>5000	Rat	ECHA Dossier				
	dermal	LD50 mg/kg	>5000	Rabbit	ECHA Dossier				
	inhalation (4 h) vapour	LC50 mg/l	(28,1)	Rat	ECHA Dossier				
67-56-1	methanol								



according to UK REACH Regulation

GYEON Q² Trim EVO

Revision date: 05.12.2023

Product code: G0043

Page 10 of 18

	oral	ATE mg/kg	100			
	dermal	ATE mg/kg	300			
	inhalation vapour	ATE	3 mg/l			
	inhalation dust/mist	ATE	0,5 mg/l			
100-41-4	ethylbenzene					
	oral	LD50 mg/kg	3500	Rat.	REACH dossier	
	dermal	LD50 mg/kg	>15000	Rabbit	REACH dossier	
	inhalation (4 h) vapour	LC50	17,2 mg/l	Rat.	REACH dossier	
	inhalation dust/mist	ATE	1,5 mg/l			
98-82-8	cumene	-				
	dermal	LD50 mg/kg	12300	Rabbit	IUCLID	
	inhalation (4 h) vapour	LC50	39 mg/l	Rat	RTECS	

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met. toluene:

In-vitro mutagenicity: Method: OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test); Result: negative. Literature information: REACH dossier; Carcinogenicity: Method: [inhalative, OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)]; Species: Rat ; Exposure duration: 2 years ; Result: NOAEC = 4522 mg/m3; Literature information: REACH dossier; Reproductive toxicity: Method: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study); Species: Rat ; Result: NOAEC = 1875 mg/m3; Literature information: REACH dossier ; Developmental toxicity/teratogenicity: Method: [inhalative, EPA OTS 798.4350 (Inhalation Developmental Toxicity Screen)]; Species: Rabbit; Exposure duration: 20d ; Result: NOEC = 2812 mg/kg; Literature information: REACH dossier

Xylene:

In-vitro mutagenicity: Method: EU Method B.10 (Mutagenicity - In Vitro Mammalian Chromosome Aberration Test); Result: negative. Literature information: REACH dossier; Developmental toxicity/teratogenicity : NOAEL >= 500ppm (OECD Guideline 414); Literature information: REACH dossier; Carcinogenicity: Method: EU Method B.32 (Carcinogenicity Test); Species: Rat.; Exposure duration: 24 months. Result: NOAEL = 500 mg/kg; Literature information: REACH dossier; Reproductive toxicity: Method: (inhalation.): EPA OPPTS 870.3800 (Reproduction and Fertility Effects); Species: Rat ; Exposure duration: 14d.Results: NOAEC = 500 ppm. Literature information: REACH dossier

n-hexane:

In-vitro mutagenicity: Method: OECD Guideline 471 (Bacterial Reverse Mutation Assay): positive (with metabolic activation). negative (without metabolic activation).; OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test): positive (without metabolic activation).; Literature information: REACH dossier In-vivo mutagenicity: Method: -; Species: Mouse.; AllgK121511: negative. Literature information: REACH dossier; Developmental toxicity/teratogenicity: Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study); Species: Rat Exposure duration: 20 d. Result: NOAEC = 704 ppm; Literature information: REACH dossier

methanol:

Germ cell mutagenicity: Method: OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test). Species: Mouse.; Result: negative. Literature information: REACH dossier; Carcinogenicity: Method: OECD Guideline



according to UK REACH Regulation

GYEON Q² Trim EVO

Revision date: 05.12.2023

Product code: G0043

Page 11 of 18

453 (Combined Chronic Toxicity / Carcinogenicity Studies). Length of test: 18 m. Species: Mouse.; Result: NOAEC = 1,3 mg/l; Literature information: REACH dossier; Reproductive toxicity: Method: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study). Species: Rat. Result: NOAEC = 1,3 mg/l; Literature information: REACH dossier; Developmental toxicity/teratogenicity: Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study). Species: Rabbit. Result: NOAEL = 1000 mg/kg.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (stoddard solvent; Low boiling point naphtha - unspecified)

toluene:

Subchronic oral toxicity: Method: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents);Species: Mouse. ; Exposure duration: 90d;Result: NOEL = 625 mg/kg ; Literature information: REACH dossier; Subchronic inhalation toxicity: Method: -; Species: Rat. Exposure duration: 1 year ;Result: NOAEC = 1131 mg/m3; Literature information: REACH dossier

Xylene: Subchronic oral toxicity: Method: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents); Species: Rat ; Exposure duration: 90d. Result: NOAEL = 750 mg/kg (male.) = 150 mg/kg (female.); Literature information: REACH dossier

n-hexane:

Subchronic oral toxicity: Method:- ; Species: Rat; Exposure duration: 90 d. Result: NOAEL = 1135mg/kg ; Literature information: REACH dossier ; Subchronic inhalation toxicity: Method OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day); Species: Mouse. Exposure duration: 90 d; Result: LOAEC = 500 ppm. Literature information: REACH dossier

methanol:

Chronic inhalative toxicity: Method: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies). Length of test: 12 m . Exposure time: 20 h/d. Species: Rat.

Result: Result: NOAEC = 1,3 mg/l. Literature information: REACH dossier

Aspiration hazard

May be fatal if swallowed and enters airways.

Specific effects in experiment on an animal

No data available.

11.2. Information on other hazards

Endocrine disrupting properties

Endocrine disrupting properties: Decamethylcyclopentasiloxane; octamethylcyclotetrasiloxane. The substance is included in one of the lists of endocrine disruptors (list II (human.)).

Other information

No data available.

SECTION 12: Ecological information

12.1. Toxicity

The product has not been tested.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
541-02-6	Decamethylcyclopentasiloxane						
	Acute fish toxicity	LC50 mg/l	> 16	96 h	Oncorhynchus mykiss (Rainbow trout)	ECHA Dossier	
	Acute algae toxicity	ErC50 mg/l	> 12		Pseudokirchneriella subcapitata	ECHA Dossier	
	Acute crustacea toxicity	EC50 mg/l	> 2,9	48 h	Daphnia magna	ECHA Dossier	
	Fish toxicity	NOEC	16 mg/l		Oncorhynchus mykiss (Rainbow trout)	ECHA Dossier	



according to UK REACH Regulation

GYEON Q² Trim EVO

Revision date: 05.12.2023

Product code: G0043

Page 12 of 18

	Algae toxicity	NOEC mg/l	> 12	4 d	Pseudokirchneriella subcapitata	ECHA Dossier				
1330-20-7	xylene	1 0								
	Acute fish toxicity	LL50 mg/l	(8,4)	96 h	Oncorhynchus mykiss	Ecotoxicology and Environmental Safety.	OECD Guideline 203			
	Acute algae toxicity	ErC50 mg/l	(4,9)	72 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety.	OECD Guideline 201			
	Acute crustacea toxicity	EL50 mg/l	(> 3,4)	48 h	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3	US EPA 600/4-91-003			
	Fish toxicity	NOEC mg/l	> 1,3	56 d	Oncorhynchus mykiss	Appl. Sci. Branch, Eng. Res. Cent. Denve	Fish were exposed in artificial streams			
	Crustacea toxicity	NOEC mg/l	1,17	7 d	Ceriodaphnia dubia	Ecotoxicology and Environmental Safety 3	US EPA 600/4-91-003			
	Acute bacteria toxicity	EC50 mg/l()	> 175	0,5 h	Activated sludge	Research Journal WPCF 60(10) 1850-1856 (OECD Guideline 209			
108-88-3	toluene									
	Acute fish toxicity	LC50 mg/l	(5,5)	96 h	Oncorhynchus kisutch	ECHA Dossier				
	Acute algae toxicity	ErC50 mg/l	(12,5)	72 h		GESTIS				
	Acute crustacea toxicity	EC50 mg/l	(3,78)		Ceriodaphnia dubia	ECHA Dossier				
	Acute bacteria toxicity	EC50 ()	134 mg/l	3 h	Chlorella vulgaris and Chlamydomonas angulosa	ECHA Dossier				
67-56-1	methanol									
	Acute fish toxicity	LC50 mg/l	15400	96 h	Lepomis macrochirus	ECHA Dossier				
	Acute algae toxicity	ErC50 mg/l	22000	96 h	Pseudokirchneriella subcapitata	Ecotoxicology and Environmental Safety 7	OECD Guideline 201			
	Acute crustacea toxicity	EC50 mg/l	> 10000	48 h	Daphnia magna	Water Research 23(4): 495-499 (1989)	DIN 38412 Teil 11			
100-41-4	ethylbenzene									
	Acute fish toxicity	LC50	5,1 mg/l	96 h	Menidia menidia	REACH dossier				
	Acute algae toxicity	ErC50	3,6 mg/l	96 h	Pseudokirchnerella subcapitata	REACH dossier				
	Acute crustacea toxicity	EC50 mg/l	1,8-2,8		Daphnia magna	REACH dossier				
	Crustacea toxicity	NOEC mg/l	0,96	7 d	Ceriodaphnia dubia	REACH dossier				
98-82-8	cumene					-	-			
	Acute fish toxicity Acute algae toxicity	LC50 ErC50	2,7 mg/l 2,6 mg/l		Leuciscus idus Selenastrum					

12.2. Persistence and degradability



according to UK REACH Regulation

GYEON Q² Trim EVO

Revision date: 05.12.2023

Product code: G0043

Page 13 of 18

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation		-		
541-02-6	Decamethylcyclopentasiloxane				
	OECD 310	0,14	28	ECHA Dossier	
	Not easily bio-degradable (according to OECD-criteria).				
1330-20-7	xylene				
	OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D	87,8%	28	OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D	
	Easily biodegradable (concerning to the criteria of the OEC	D)			
67-56-1	methanol				
	other guideline	76%	20	ECHA Dossier	
	Easily biodegradable (concerning to the criteria of the OEC	D)			
100-41-4	ethylbenzene				
	ISO 14593-CO2-Headspace Test	79	28	REACH dossier	
	Easily biodegradable (concerning to the criteria of the OECD)				

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
541-02-6	Decamethylcyclopentasiloxane	8,023
546-68-9	Titanium tetraisopropanolate	0,05
1330-20-7	xylene	3,2
108-88-3	toluene	2,73
67-56-1	methanol	-0,77
100-41-4	ethylbenzene	3,6
98-82-8	cumene	3,66

BCF

CAS No	Chemical name	BCF	Species	Source
541-02-6	Decamethylcyclopentasiloxane	7060	Pimephales promelas	ECHA
1330-20-7	xylene	5,5 - 12,2	Oncorhynchus mykiss	Appl. Sci. Branch, E
67-56-1	methanol	1	Cyprinus carpio	Comparative Biochemi

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The mixture contains the following substances fulfilling the PBT criteria according to UK REACH: Hexamethyldisiloxane; octamethylcyclotetrasiloxane.

The mixture contains the following substances fulfilling the vPvB criteria according to UK REACH: Decamethylcyclopentasiloxane; octamethylcyclotetrasiloxane.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1 %.

12.7. Other adverse effects

No data available.

according to UK REACH Regulation

GYEON Q² Trim EVO

Revision date: 05.12.2023

Product code: G0043

Page 14 of 18

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Consult the local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. According to (EWC) European Waste Catalogue, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to (EWC) European Waste Catalogue:

List of Wastes Code - residues/unused products

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances; hazardous waste

List of Wastes Code - used product

160305 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; off-specification batches and unused products; organic wastes containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (Aminoalkoxydimethylpolysiloxane,
	stoddard solvent; Low boiling point naphtha - unspecified)
14.3. Transport hazard class(es):	3
14.4. Packing group:	
Hazard label:	3
Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (Aminoalkoxydimethylpolysiloxane,
	stoddard solvent; Low boiling point naphtha - unspecified)
14.3. Transport hazard class(es):	3
14.4. Packing group:	11
Hazard label:	3

Revision date: 05.12.2023

Safety Data Sheet

according to UK REACH Regulation

GYEON Q² Trim EVO

Product code: G0043

Page 15 of 18

Classification code:		
Special Provisions:		
Limited quantity:		
Excepted quantity:		

Marine transport (IMDG)

14.1. UN number or ID number: 14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

Н	lazaro	l la	be	1:

Marine pollutant:
Special Provisions:
Limited quantity:
Excepted quantity:
EmS:

Air transport (ICAO-TI/IATA-DGR) 14.1. UN number or ID number: 14.2. UN proper shipping name:

14.3. Transport hazard class(es) 14.4. Packing group:

II
3
NO
274
1 L
E2

FLAMMABLE LIQUID, N.O.S. (Aminoalkoxydimethylpolysiloxane, stoddard solvent; Low boiling point naphtha - unspecified)

UN 1993 FLAMMABLE LIQUID, N.O.S. (Aminoalkoxydimethylpolysiloxane,

353

5 I 364

60 L

stoddard solvent; Low boiling point naphtha - unspecified)

14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Special Provisions:	A3
Limited quantity Passenger:	1 L
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	
IATA-max. quantity - Passenger:	
IATA-packing instructions - Cargo:	

F1

1 L E2

3

UN 1993

F-E, S-E

274 601 640D

14.5. Environmental hazards

IATA-max. quantity - Cargo:

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

See section 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information



according to UK REACH Regulation

GYEON Q² Trim EVO

work protection guideline' (94/33/EC).

2 - obviously hazardous to water

Observe restrictions to employment for juveniles according to the 'juvenile

Revision date: 05.12.2023

Product code: G0043

Page 16 of 18

Authorisations (REACH, annex XIV): Substances of very high concern, SVHC (REACH, article 59): Decamethylcyclopentasiloxane; octamethylcyclotetrasiloxane

 Restrictions on use (REACH, annex XVII):

 Entry 3, Entry 40, Entry 48, Entry 69, Entry 70, Entry 75

 Directive 2010/75/EU on industrial
 No information available.

 emissions:
 Directive 2004/42/EC on VOC in

 Directive 2004/42/EC on VOC in
 No information available.

 paints and varnishes:
 No information available.

 Information according to Directive
 P5c FLAMMABLE LIQUIDS

 2012/18/EU (SEVESO III):
 No

Additional information

Safety Data Sheet according to UK-REACH Regulation The mixture is classified as hazardous according to GHS (GB CLP). UK REACH Appendix XVII, No (mixture): 3, 40, 48, 69, 70

National regulatory information

Employment restrictions:

Water hazard class (D):

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

Rev. 1,0; 06.06.2015, Initial release Rev. 1.1; 01.09.2016, Changes in chapter: 1,16. Rev. 2.0; 08.03.2019, Changes in chapter: 1 - 16. Rev. 3.0; 11.05.2020, Revision Changes in chapter: 1 - 16 Rev. 3.1; 05.02.2021, Revision Rev. 4.0; 20.05.2021, Revision Changes in chapter: 1 - 16 Rev. 4.1; 01.09.2021, Revision 2,3,15,16 Rev. 5.0; 02.01.2023, Revision Changes in chapter: 1 - 16 Rev. 6.0; 17.10.2023, Revision

according to UK REACH Regulation

GYEON Q² Trim EVO

Revision date: 05.12.2023

Product code: G0043

Page 17 of 18

Abbreviations and acronyms Flam. Liq: Flammable liquids Acute Tox: Acute toxicity Asp. Tox: Aspiration hazard Skin Irrit: Skin irritation Eye Irrit: Eye irritation Carc: Carcinogenicity Repr: Reproductive toxicity STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) CAS: Chemical Abstracts Service CLP: Classification, Labelling and Packaging of substances and mixtures DNEL: Derived No Effect Level d: dav(s) EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances ECHA: European Chemicals Agency EWC: European Waste Catalogue IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organization ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) GHS: Globally Harmonized System of Classification and Labelling of Chemicals GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany) h. pon I OAFL: I owest observed adverse effect level LOAEC: Lowest observed adverse effect concentration LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NOAEL: No observed adverse effect level NOAEC: No observed adverse effect concentration NLP: No-Longer Polymers N/A: not applicable OECD: Organisation for Economic Co-operation and Development PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) REACH: Registration, Evaluation, Authorisation of Chemicals SVHC: substance of very high concern TRGS: Technische Regeln für Gefahrstoffe UN: United Nations VOC: Volatile Organic Compounds



according to UK REACH Regulation

GYEON Q² Trim EVO

Revision date: 05.12.2023

Product code: G0043

Page 18 of 18

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT RE 2; H373	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

e	elevant H and EOH statements (number and run text)		
	H225	Highly flammable liquid and vapour.	
	H226	Flammable liquid and vapour.	
	H301	Toxic if swallowed.	
	H304	May be fatal if swallowed and enters airways.	
	H311	Toxic in contact with skin.	
	H312	Harmful in contact with skin.	
	H315	Causes skin irritation.	
	H319	Causes serious eye irritation.	
	H331	Toxic if inhaled.	
	H332	Harmful if inhaled.	
	H335	May cause respiratory irritation.	
	H336	May cause drowsiness or dizziness.	
	H350	May cause cancer.	
	H361d	Suspected of damaging the unborn child.	
	H361f	Suspected of damaging fertility.	
	H370	Causes damage to organs.	
	H372	Causes damage to organs through prolonged or repeated exposure.	
	H373	May cause damage to organs through prolonged or repeated exposure.	
	H400	Very toxic to aquatic life.	
	H410	Very toxic to aquatic life with long lasting effects.	
	H411	Toxic to aquatic life with long lasting effects.	
	H412	Harmful to aquatic life with long lasting effects.	

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)