



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Wheel Sealant

Print date: 28.06.2016

Product code:

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Wheel Sealant

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Automotive care products

Uses advised against

any non-intended use.

1.3. Details of the supplier of the safety data sheet

Company name:	Poorboys World UK	
	Unit 1 Bretfield Court	
Street:	Off Bretton Street	
Place:	GB-WF12 9BG Dewsbury	
Telephone:	+44 (0) 1924 469920	
Internet:	http://poorboysworld.com/	
Responsible Department:	Dr. Gans-Eichler	e-mail: info@tge-consult.de
	Chemieberatung GmbH	Tel.: +49 (0)251/924520-60
	Raesfeldstr. 22	www.tge-consult.de
	D-48149 Münster	

1.4. Emergency telephone number:

1-352-323-3500 International Emergency Hotline

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Harmful to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Distillates (petroleum), hydrotreated light, Kerosine - unspecified

Signal word: Warning

Pictograms:



Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Wheel Sealant

Print date: 28.06.2016

Product code:

Page 2 of 11

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves and eye/face protection.
P405 Store locked up.
P501 Dispose of contents/container to local/regional/national/international regulations.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-47-8	Distillates (petroleum), hydrotreated light, Kerosine - unspecified			55 - < 60 %
	265-149-8	649-422-00-2		
	Flam. Liq. 3, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1; H226 H315 H336 H304			
63148-62-9	dimethyl silicone			1 - 5 %
	Skin Irrit. 2, Eye Irrit. 2, Aquatic Chronic 2; H315 H319 H411			
93-83-4	N,N-bis(2-hydroxyethyl)oleamide			1 - 5 %
	202-281-7			
	Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H315 H319 H335			

Full text of H and EUH statements: see section 16.

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons, < 5 % non-ionic surfactants, perfumes, preservation agents (Formaldehyde).

Further Information

Product does not contain listed SVHC substances > 0,1 % according to Regulation (EC) No. 1907/2006 Article 59 (REACH)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In case of respiratory tract irritation, consult a physician.

After contact with skin

Gently wash with plenty of soap and water. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse cautiously with water for several minutes. In case of troubles or persistent symptoms, consult an ophthalmologist.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Wheel Sealant

Print date: 28.06.2016

Product code:

Page 3 of 11

After ingestion

Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Do NOT induce vomiting.
In all cases of doubt, or when symptoms persist, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Dry extinguishing powder. Alcohol resistant foam. Atomized water.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide Carbon dioxide. Nitrogen oxides (NO_x).

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.
Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

See protective measures under point 7 and 8.
Do not breathe vapour/aerosol. Avoid contact with eyes and skin.

6.2. Environmental precautions

Discharge into the environment must be avoided.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).
Treat the recovered material as prescribed in the section on waste disposal.
Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Wear suitable protective clothing. See section 8.
Conditions to avoid : generation/formation of aerosols

Advice on protection against fire and explosion

Usual measures for fire prevention.

Further information on handling

General protection and hygiene measures: refer to chapter 8

7.2. Conditions for safe storage, including any incompatibilities



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Wheel Sealant

Print date: 28.06.2016

Product code:

Page 4 of 11

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Advice on storage compatibility

Do not store together with: Explosives. Oxidizing solids. Oxidizing liquids. Radioactive substances. Infectious substances. Food and feedingstuffs.

Further information on storage conditions

Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

Recommended storage temperature: 20°C

Protect against: Light. UV-radiation/sunlight. heat. moisture.

7.3. Specific end use(s)

refer to chapter 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
8002-74-2	Paraffin wax, fume	-	2		TWA (8 h)	WEL
		-	6		STEL (15 min)	WEL

Additional advice on limit values

air limit values:

Possibility of exposure to Aerosol

Limit value = 5 mg/m³ - Source: ACGIH

8.2. Exposure controls



Appropriate engineering controls

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Protective and hygiene measures

Always close containers tightly after the removal of product. When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work.

Eye/face protection

Wear safety glasses; chemical goggles (if splashing is possible).

Hand protection

In case of prolonged or frequently repeated skin contact:

Wear suitable gloves.

Suitable material:

FKM (fluororubber). - Thickness of glove material: 0,4 mm

Breakthrough time \geq 8 h

Butyl rubber. - Thickness of glove material: 0,5 mm

Breakthrough time \geq 8 h

CR (polychloroprenes, Chloroprene rubber). - Thickness of glove material: 0,5 mm

Breakthrough time \geq 8 h

NBR (Nitrile rubber). - Thickness of glove material: 0,35 mm

Breakthrough time \geq 8 h



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Wheel Sealant

Print date: 28.06.2016

Product code:

Page 5 of 11

PVC (Polyvinyl chloride). - Thickness of glove material: 0,5 mm

Breakthrough time \geq 8 h

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Check leak tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Suitable protective clothing: Lab apron.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Environmental exposure controls

No special precautionary measures are necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	pink
Odour:	characteristic

Test method

pH-Value:	not determined
-----------	----------------

Changes in the physical state

Melting point:	not determined
Initial boiling point and boiling range:	>65 °C
Sublimation point:	not determined
Softening point:	not determined
Pour point:	not determined
Flash point:	82 °C closed cup
Sustaining combustion:	Not sustaining combustion

Explosive properties

none

Lower explosion limits:	not determined
Upper explosion limits:	not determined
Ignition temperature:	not determined

Auto-ignition temperature

Gas:	not determined
Decomposition temperature:	not determined

Oxidizing properties

none

Vapour pressure: (at 25 °C)	not determined
Density (at 25 °C):	1,11 g/cm ³
Water solubility:	not determined

Solubility in other solvents

not determined

Partition coefficient:	not determined
------------------------	----------------



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Wheel Sealant

Print date: 28.06.2016

Product code:

Page 6 of 11

Viscosity / dynamic:	not determined
Viscosity / kinematic:	not determined
Flow time:	not determined
Vapour density:	not determined
Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	not determined

9.2. Other information

Solid content:	not determined
----------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Protect against: UV-radiation/sunlight. heat.

10.5. Incompatible materials

Materials to avoid: Oxidizing agents, strong. Reducing agents, strong.

10.6. Hazardous decomposition products

In case of fire may be liberated: Carbon monoxide Carbon dioxide. Nitrogen oxides (NOx).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicokinetics, metabolism and distribution

No data available.

Acute toxicity

Based on available data, the classification criteria are not met.

The product has not been tested.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Wheel Sealant

Print date: 28.06.2016

Product code:

Page 7 of 11

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
64742-47-8	Distillates (petroleum), hydrotreated light, Kerosine - unspecified			
	oral	LD50 > 5000 mg/kg	Rat	ECHA dossier
	dermal	LD50 > 2000 mg/kg	Rabbit.	ECHA dossier
	inhalative (4 h) vapour	LC50 (> 5,3) mg/l	Rat	ECAH dossier
63148-62-9	dimethyl silicone			
	oral	LD50 >17000 mg/kg	Rat	RTECS
	dermal	LD50 >2000 mg/kg	Rabbit	RTECS
93-83-4	N,N-bis(2-hydroxyethyl)oleamide			
	oral	LD50 >10000 mg/kg	Mouse	RTECS
	dermal	LD50 >10000 mg/kg	Rat	RTECS

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

The product has not been tested.

dimethyl silicone:

Skin corrosion/irritation: 500 µl/24h, Rabbit

Result / evaluation: slightly irritant

Irritant effect on the eye: 500 µl/24h, Rabbit

Result / evaluation: slightly irritant

Sensitising effects

Based on available data, the classification criteria are not met.

The product has not been tested.

The product is not: sensitising

The statement is derived from the properties of the single components.

Carcinogenic/mutagenic/toxic effects for reproduction



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Wheel Sealant

Print date: 28.06.2016

Product code:

Page 8 of 11

Based on available data, the classification criteria are not met.
Distillates (petroleum), hydrotreated light, Kerosine - unspecified:

In vitro mutagenicity/genotoxicity:

Method:

-OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells)

-OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

-OECD Guideline 471 (Bacterial Reverse Mutation Assay)

Result: negative.

literature information: ECHA Dossier

In vivo mutagenicity/genotoxicity:

Method:

-OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)

-OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)

Result: negative.

literature information: ECHA Dossier

Reproductive toxicity

Method:-

Species: Sprague-Dawley Rat

Exposure route : oral

Result: NOAEL > 1500 mg/kg

literature information: ECHA Dossier

Developmental toxicity/teratogenicity

Method:OECD Guideline 414 (Prenatal Developmental Toxicity Study)

Species: Sprague-Dawley Rat

Exposure route : oral

Result: NOAEL = 1000 mg/kg

literature information: ECHA Dossier

STOT-single exposure

May cause drowsiness or dizziness. (Distillates (petroleum), hydrotreated light, Kerosine - unspecified)

Distillates (petroleum), hydrotreated light, Kerosine - unspecified:

Subchronic oral toxicity:

Method:-

Species: Sprague-Dawley Rat ;Exposure duration: 90d

Result: NOAEL = 750 mg/kg ; literature information: ECHA Dossier

Subchronic inhalation toxicity :

Method:OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

Species: Mouse ; Exposure duration: 90d

Result: NOAEC = 1000 mg/kg ; literature information: ECHA Dossier

Subchronic oral toxicity:

Method: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Species: Sprague-Dawley Rat ; Exposure duration: 28d

Result: NOAEC = 0,5 ml/kg; literature information: ECHA Dossier

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No data available.

SECTION 12: Ecological information

12.1. Toxicity



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Wheel Sealant

Print date: 28.06.2016

Product code:

Page 9 of 11

The product has not been tested.

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-47-8	Distillates (petroleum), hydrotreated light, Kerosine - unspecified			
	OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D	61 %	28	ECHA Dossier
	The product is readily biodegradable to OECD criteria.			

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No data available.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Observe in addition any national regulations! Consult the local waste disposal expert about waste disposal.

Non-contaminated packages may be recycled.

According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Control report for waste code/ waste marking according to EAKV:

Waste disposal number of waste from residues/unused products

200129 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); detergents containing hazardous substances
Classified as hazardous waste.

Waste disposal number of used product

200129 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); detergents containing hazardous substances
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150203 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; absorbents, filter materials, wiping cloths and protective clothing; absorbents, filter materials, wiping cloths and protective clothing other than those mentioned in 15 02 02

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Wheel Sealant

Print date: 28.06.2016

Product code:

Page 10 of 11

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Air transport (ICAO)

14.1. UN number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

refer to chapter 6-8

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC):	No information available.
2004/42/EC (VOC):	No information available.
Information according to 2012/18/EU (SEVESO III):	Not subject to 2012/18/EU (SEVESO III)

Additional information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].
REACH 1907/2006 Appendix XVII, No (mixture): 3

National regulatory information

Employment restrictions:	Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
Water contaminating class (D):	1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Wheel Sealant

Print date: 28.06.2016

Product code:

Page 11 of 11

Rev. 1.0; Initial release: 28.06.2016

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

CAS Chemical Abstracts Service

DNEL: Derived No Effect Level

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect level

NTP: National Toxicology Program

N/A: not applicable

OSHA: Concerning the International Transport of Dangerous Goods by Rail)

PNEC: predicted no effect concentration

PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

SARA: Superfund Amendments and Reauthorization Act

SVHC: substance of very high concern

TRGS Technische Regeln für Gefahrstoffe

TSCA: Toxic Substances Control Act

VOC: Volatile Organic Compounds

VwVwS: Verwaltungsvorschrift wassergefährdender Stoffe

WGK: Wassergefährdungsklasse

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)