

SAFETY DATA SHEET

US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Issuing Date 12-Jan-2022 Revision Date 12-Jan-2022 Revision Number 1

1. Identification

Product identifier

Product Name Mothers Ultimate Mag & Aluminum Polish

Other means of identification

Product Code(s) 05120, 35120

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use Car care

Restrictions on use No information available

Details of the supplier of the safety data sheet

Supplier Address

MOTHERS POLISHES WAXES CLEANERS 5456 Industrial Drive

Huntington Beach, CA 92649

T: 714-891-3364 F: 714-893-1827

E-mail info@mothers.com

Emergency telephone number

Emergency telephone CHEMTREC: +1-703-527-3887 (INTERNATIONAL)

1-800-424-9300 (NORTH AMERICA)

2. Hazard(s) identification

Classification

Serious eye damage/eye irritation	Category 2A
Aspiration hazard	Category 1

Label elements

Danger

Hazard statements

Causes serious eye irritation.

May be fatal if swallowed and enters airways.

·



Precautionary Statements - Prevention

Avoid breathing vapors. Wash face, hands and any exposed skin thoroughly after handling. Wear eye and face protection.

Precautionary Statements - Response

Eves

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice and attention.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

Precautionary Statements - Storage

Store locked up.

Precautionary Statements - Disposal

Dispose of contents and container to an approved waste disposal plant.

Other information

Causes mild skin irritation.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Petroleum distillates, hydrotreated light	64742-47-8	30 - 40	-	-
Alumina	1344-28-1	20 - 30	-	-
Stearic acid	57-11-4	5 - 10	-	-
Triethanolamine	102-71-6	1 - 5	-	-
Alcohols, C10-16, ethoxylated	68002-97-1	1 - < 3	-	-
Hexylene glycol	107-41-5	1 - 5	-	-
Ethyl silicate	78-10-4	1 - 5	-	-

4. First-aid measures

Description of first aid measures

General advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Inhalation Aspiration into lungs can produce severe lung damage. If breathing has stopped, give

artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult,

(trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed

Revision Date: 12-Jan-2022

pulmonary edema may occur.

Eve contactRinse immediately with plenty of water, also under the evelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

persists.

Skin contactWash skin with soap and water. In the case of skin irritation or allergic reactions see a

physician.

Ingestion ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE.

Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth. Never give anything by mouth to an unconscious person.

Get immediate medical advice/attention.

Self-protection of the first aider Avoid breathing vapors. Ensure that medical personnel are aware of the material(s)

involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and

tearing of the eyes. Burning sensation. Prolonged contact may cause redness and irritation.

Indication of any immediate medical attention and special treatment needed

Note to physicians Because of the danger of aspiration, emesis or gastric lavage should not be employed

unless the risk is justified by the presence of additional toxic substances.

5. Fire-fighting measures

Suitable Extinguishing Media Dry chemical, CO2, water spray or regular foam.

Unsuitable extinguishing media None known based on information supplied.

Specific hazards arising from the

chemical

None known based on information supplied.

Hazardous combustion products Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

Explosion data

Sensitivity to mechanical impact None. Sensitivity to static discharge None.

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact

with skin, eyes or clothing.

Other information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Take up mechanically, placing in appropriate containers for disposal.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection

Control parameters

Exposure Limits

Chemical name	ACGIH TLV		OSH	A PEL		NIOSH		
Alumina 1344-28-1	TWA: 1 mg/m³ resp particulate matte	tter TWA: 5		/m ³ total dust m ³ respirable ction : 10 mg/m ³ total		-		
			(vacated) T	ust WA: 5 mg/m ³ le fraction				
Stearic acid 57-11-4	particulate matte	alable - er irable		TWA: 10 mg/m³ inhalable - particulate matter TWA: 3 mg/m³ respirable				-
Triethanolamine 102-71-6	TWA: 5 mg/m ³	3				-		
Hexylene glycol 107-41-5	STEL: 50 ppm vapor STEL: 10 mg/m³ inh particulate matter, aero TWA: 25 ppm vapor	alable (vacated) Ceiling: 125 n			Ceiling: 25 ppm Ceiling: 125 mg/m³			
Ethyl silicate 78-10-4	TWA: 10 ppm	TWA: 1 TWA: 85 (vacated) T		100 ppm 50 mg/m³ WA: 10 ppm WA: 85 mg/m³		IDLH: 700 ppm TWA: 10 ppm TWA: 85 mg/m ³		
Chemical name	Alberta	Britis	h Columbia	Ontario		Quebec		
Alumina 1344-28-1	TWA: 10 mg/m ³		: 1.0 mg/m ³	TWA: 1 mg/		TWA: 10 mg/m ³		
Stearic acid 57-11-4	-	TWA: 10 mg/m ³ TWA: 3 mg/m ³		TWA: 10 mg TWA: 3 mg/		TWA: 10 mg/m ³		
Triethanolamine 102-71-6	TWA: 5 mg/m ³	TW	A: 5 mg/m ³	TWA: 0.5 pp TWA: 3.1 mg		TWA: 5 mg/m ³		
Hexylene glycol 107-41-5	Ceiling: 25 ppm Ceiling: 121 mg/m³		ng: 25 ppm	TWA: 25 pp STEL: 50 pp STEL: 10 mg	om	Ceiling: 25 ppm Ceiling: 121 mg/m³		
Ethyl silicate 78-10-4	TWA: 10 ppm TWA: 85 mg/m ³	TW	A: 10 ppm	TWA: 10 pp	om	TWA: 10 ppm TWA: 85 mg/m³		

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear suitable gloves.

Skin and body protectionWear suitable protective clothing.

Respiratory protectionNo protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

No data available

No data available

No data available

Revision Date: 12-Jan-2022

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do

not eat, drink or smoke when using this product.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance

Physical state Solid
Color White
Odor None

Odor threshold No information available

Property Values Remarks • Method

pH No data available

Melting point / freezing point 55 °C / 131 °F

Initial boiling point and boiling

range

Flash point No data available
Evaporation rate No data available
Flammability No data available

Flammability Limit in Air

Upper flammability or explosive

limits

Lower flammability or explosive

limits

No data available Vapor pressure Vapor density No data available Relative density No data available Water solubility No data available Solubility(ies) No data available Partition coefficient No data available No data available **Autoignition temperature** No data available **Decomposition temperature** Kinematic viscosity No data available **Dynamic viscosity** No data available

Other information

Explosive properties
Oxidizing properties
No information available.
No information available.
No information available.
No information available

10. Stability and reactivity

Reactivity None under normal use conditions.

Mothers Ultimate Mag & Aluminum Polish

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

Conditions to avoid Incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products Carbon monoxide. Carbon dioxide (CO2).

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Aspiration into lungs can

produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be

fatal. May cause irritation of respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation.

(based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. Prolonged contact may

cause redness and irritation. Causes mild skin irritation. Repeated exposure may cause

skin dryness or cracking.

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and

tearing of the eyes. Prolonged contact may cause redness and irritation.

Acute toxicity

Numerical measures of toxicity

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Chemical name	Oral LD30	Definial LD30	
Petroleum distillates, hydrotreated light	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h
Alumina	> 5000 mg/kg (Rat)	-	-
Stearic acid	= 4600 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Triethanolamine	= 4190 mg/kg (Rat)	> 20000 mg/kg (Rabbit)	-
Hexylene glycol	= 3700 mg/kg (Rat)	= 12300 mg/kg (Rabbit)	-
Ethyl silicate	= 6270 mg/kg (Rat)	= 5878 mg/kg (Rabbit)	= 10 mg/L (Rat) 4 h
			> 16.8 mg/L (Rat)4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Triethanolamine	-	Group 3	-	-
102-71-6		·		

Legend

IARC (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicityNo information available.

STOT - single exposure No information available.

STOT - repeated exposureNo information available.

Aspiration hazard May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
Datralaum diatillatas	Ostroloum distillatos		microorganisms	
Petroleum distillates,	_	LC50: =2.2mg/L (96h,	-	·
hydrotreated light 64742-47-8		Lepomis macrochirus) LC50: =2.4mg/L (96h,		
04/42-47-0		Oncorhynchus mykiss)		
		LC50: =45mg/L (96h,		
		Pimephales promelas)		
Triathanalamina	FCF0: 460mm/l (00h	LC50: 10600 -		
Triethanolamine 102-71-6	EC50: =169mg/L (96h, Desmodesmus		-	-
102-71-6		13000mg/L (96h,		
	subspicatus)	Pimephales promelas) LC50: 450 - 1000mg/L		
	EC50: =216mg/L (72h, Desmodesmus			
		(96h, Lepomis		
	subspicatus)	macrochirus) LC50: >1000mg/L (96h,		
		Pimephales promelas)		
Hexylene glycol		LC50: 10500 -		EC50: 2700 - 3700mg/L
107-41-5	_	11000mg/L (96h,	_	(48h, Daphnia magna)
107-41-5		Pimephales promelas)		(4611, Daprillia Illaglia)
		LC50: =10000mg/L		
		(96h, Lepomis		
		macrochirus)		
		LC50: =10700mg/L		
		(96h, Pimephales		
		promelas)		
		LC50: =8690mg/L (96h,		
		Pimephales promelas)		
Ethyl silicate	_	LC50: >245mg/L (96h,	-	_
78-10-4		Danio rerio)		

Persistence and degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Triethanolamine 102-71-6	-2.53
Hexylene glycol	0.14
107-41-5	

Mobility in soil No information available.

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

products

Waste from residues/unused

Dispose of in accordance with local regulations, Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

14. Transport information

DOT Not regulated

TDG Not regulated

<u>IATA</u> Not regulated

IMDG Not regulated

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

Contact supplier for inventory compliance status

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
Alumina - 1344-28-1	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Alumina 1344-28-1	X	X	X
Triethanolamine 102-71-6	X	X	X
Hexylene glycol 107-41-5	X	X	Х
Ethyl silicate 78-10-4	X	X	Х
Diethylene glycol monoethyl ether 111-90-0	Х	-	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPAHealth hazards2Flammability0Instability0Special hazards-HMISHealth hazards2Flammability0Physical hazards0Personal protectionX

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

Key literature references and sources for data used to compile the SDS

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan GHS Classification

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program

Organization for Economic Co-operation and Development Screening Information Data Set

World Health Organization

Issuing Date 12-Jan-2022

Revision Date 12-Jan-2022

Revision Note Initial Release.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet